



LT2WRH150-00-1-G-24V

LED tunnel light, 150x183 mm, green, 24V

SPECIFICATIONS

Optical specifications

| | | |
|------------------------------|------|--------------|
| Light color, peak wavelength | | green, 525nm |
| Working distance | (mm) | 40 - 60 |
| Lighting area | | |
| Length | (mm) | 74 |
| Width | (mm) | 147 |

Electrical specifications

| | | |
|------------------------------|---|------|
| Illumination extension cable | Extension cable must be ordered separately 4 | |
| Continuous mode | | |
| Supply voltage | (V) | 24 |
| Current | (mA) | 400 |
| Power consumption | W | 9.6 |
| Pulsed mode | | |
| Supply voltage 1 | (V) | 36 |
| Max pulse current 2 | (mA) | 1200 |

Mechanical specifications

| | | |
|----------------|------|-------------|
| Width x Length | (mm) | 177.6 x 163 |
| Aperture | (mm) | 25 |
| Height | (mm) | 106.5 |

Environment

| | |
|-----------|----|
| IP rating | 00 |
|-----------|----|

NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

ORDERING INFORMATION

All accessories including lighting extension cables (CB series), diffusers (DFLT series), polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

COMPATIBLE PRODUCTS



| | |
|-------------------|---|
| MC4K100X-F | Macro lens for 4k linescan cameras, magnification 1.00x, F-mount |
| MC4K100X-N | Macro lens for 4k linescan cameras, magnification 1.00x, mount M42X1 FD = 10.56 |



| | |
|--------------------|---|
| LTDV1CH-17V | Strobe controller 1 channel variable current 5 mA - 17A |
|--------------------|---|

