

# LT2WRH200-00-1-W-24V

LED tunnel light, 200x183 mm, white, 24V

OPTO ENGINEERING

## SPECIFICATIONS

### Optical specifications

Light color, peak wavelength		white, 6300K
Working distance	(mm)	40 - 60
Lighting area		
Length	(mm)	124
Width	(mm)	147

### Electrical specifications

Illumination extension cable	Extension cable must be ordered separately <b>4</b>	
------------------------------	-----------------------------------------------------	--

### Continuos mode

Supply voltage	(V)	24
Current	(mA)	400
Power consumption	W	9.6

### Pulsed mode

Supply voltage <b>1</b>	(V)	36
Max pulse current <b>2</b>	(mA)	1200

### Mechanical specifications

Width x Length	(mm)	227 x 163
Aperture	(mm)	25
Height	(mm)	131.5

### Environment

IP rating	00
-----------	----

## NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

## ORDERING INFORMATION

All accessories including lighting extension cables (CB series), diffusers (DFLT series), polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

### COMPATIBLE PRODUCTS



<b>MC4K050X-F</b>	Macro lens for 4k linescan cameras, magnification 0.50x, F-mount
<b>MC4K050X-N</b>	Macro lens for 4k linescan cameras, magnification 0.50x, mount M42X1 FD = 10.56
<b>MC4K075X-F</b>	Macro lens for 4k linescan cameras, magnification 0.75x, F-mount
<b>MC4K075X-N</b>	Macro lens for 4k linescan cameras, magnification 0.75x, mount M42X1 FD = 10.56



<b>LTDV1CH-17V</b>	Strobe controller 1 channel variable current 5 mA - 17A
--------------------	---------------------------------------------------------

