

LT4WRG250-00-1-R-24V

LED dome light, 284 mm outer diameter, red, 24V

SPECIFICATIONS

Optical specifications

Light color, peak wavelength		red, 630nm
Working distance	(mm)	50 - 100

Lighting area

Illumination area diameter	(mm)	212
----------------------------	------	-----

Electrical specifications

Illumination extension cable	Extension cable must be ordered separately 4	
------------------------------	--	--

Continuos mode

Supply voltage	(V)	24
Current	(mA)	476
Power consumption	W	11.5

Pulsed mode

Supply voltage 1	(V)	36
Max pulse current 2	(mA)	1428

Mechanical specifications

Outer diameter	(mm)	284
Aperture range	(mm)	50
Height	(mm)	139,4

Environment

IP rating		00
-----------	--	----

NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

COMPATIBLE PRODUCTS



LTDV1CH-17V	Strobe controller 1 channel variable current 5 mA - 17A
--------------------	---



CMLT4WRG250-00-1	Bracket for LT4WRG250
-------------------------	-----------------------

