

# LTZGK070-15-3-R-24V

LED ringlight, 3 LED rows, outer diameter 70 mm, 15°, red, 24V

## SPECIFICATIONS

### Optical specifications

Light color, peak wavelength		red, 630nm
Working distance	(mm)	85
Lighting area		
Inner	(mm)	37
Outer	(mm)	67
Emission angle	(deg)	15

### Electrical specifications

Illumination extension cable	Extension cable must be ordered separately <b>4</b>	
------------------------------	---	--

#### Continuous mode

Supply voltage	(V)	24
Current	(mA)	180
Power consumption	W	4.4

#### Pulsed mode

Supply voltage <b>1</b>	(V)	36
Max pulse current <b>2</b>	(mA)	540

### Mechanical specifications

Inner diameter	(mm)	32
Outer diameter	(mm)	70
Height	(mm)	20,5

### Environment

IP rating	00
-----------	----

## NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

## ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

### COMPATIBLE PRODUCTS



**LTDV1CH-17V** Strobe controller 1 channel variable current 5 mA - 17A



**DFLTZGK070-15-3** Diffuser for LED ringlight, 3 LED rows, outer diameter 70 mm, 15°



**PLLTZGK070-15-3** Polarizer for LED ringlight, 3 LED rows, outer diameter 70 mm, 15°

