



LTZGK070-15-3-W-24V

LED ringlight, 3 LED rows, outer diameter 70 mm, 15°, white, 24V

SPECIFICATIONS

Optical specifications

Light color, peak wavelength		white, 6300K
Working distance	(mm)	85
Lighting area		
Inner	(mm)	37
Outer	(mm)	67
Emission angle	(deg)	15

Electrical specifications

Illumination extension cable	Extension cable must be ordered separately 4	
------------------------------	---	--

Continuous mode

Supply voltage	(V)	24
Current	(mA)	240
Power consumption	W	5.8

Pulsed mode

Supply voltage 1	(V)	36
Max pulse current 2	(mA)	720

Mechanical specifications

Inner diameter	(mm)	32
Outer diameter	(mm)	70
Height	(mm)	20,5

Environment

IP rating	00
-----------	----






NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

COMPATIBLE PRODUCTS

	LTDV1CH-17V Strobe controller 1 channel variable current 5 mA - 17A
	DFLTZGK070-15-3 Diffuser for LED ringlight, 3 LED rows, outer diameter 70 mm, 15°
	PLLTZGK070-15-3 Polarizer for LED ringlight, 3 LED rows, outer diameter 70 mm, 15°