



# LTZGK100-15-5-W-24V

LED ringlight, 5 LED rows, outer diameter 103 mm, 15°, white, 24V

## SPECIFICATIONS

### Optical specifications

Light color, peak wavelength		white, 6300K
Working distance	(mm)	128
Lighting area		
Inner	(mm)	53
Outer	(mm)	99
Emission angle	(deg)	15

### Electrical specifications

Illumination extension cable	Extension cable must be ordered separately <b>4</b>	
Continuous mode		
Supply voltage	(V)	24
Current	(mA)	570
Power consumption	W	13.7
Pulsed mode		
Supply voltage <b>1</b>	(V)	36
Max pulse current <b>2</b>	(mA)	1710

### Mechanical specifications

Inner diameter	(mm)	48
Outer diameter	(mm)	103
Height	(mm)	24

### Environment

IP rating	00
-----------	----



## NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

## ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

### COMPATIBLE PRODUCTS



**LTDV1CH-17V** Strobe controller 1 channel variable current 5 mA - 17A



**DFLTZGK100-15-5** Diffuser for LED ringlight, 5 LED rows, outer diameter 103 mm, 15°



**PLLTZGK100-15-5** Polarizer for LED ringlight, 5 LED rows, outer diameter 103 mm, 15°