



LTZGK100-45-5-B-24V

LED ringlight, 5 LED rows, outer diameter 100 mm, 45°, blue, 24V

SPECIFICATIONS

Optical specifications

Light color, peak wavelength		blue, 470nm
Working distance	(mm)	24
Lighting area		
Inner	(mm)	58
Outer	(mm)	95
Emission angle	(deg)	45

Electrical specifications

Illumination extension cable	Extension cable must be ordered separately 4	
------------------------------	---	--

Continuos mode

Supply voltage	(V)	24
Current	(mA)	600
Power consumption	W	14.4

Pulsed mode

Supply voltage 1	(V)	36
Max pulse current 2	(mA)	1800

Mechanical specifications

Inner diameter	(mm)	48
Outer diameter	(mm)	100
Height	(mm)	30

Environment

IP rating		00
-----------	--	----



NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

COMPATIBLE PRODUCTS



LTDV1CH-17V Strobe controller 1 channel variable current 5 mA - 17A