

# LTZGK100-45-5-G-24V

LED ringlight, 5 LED rows, outer diameter 100 mm, 45°, green, 24V

## SPECIFICATIONS

### Optical specifications

Light color, peak wavelength		green, 525nm
Working distance	(mm)	24
Lighting area		
Inner	(mm)	58
Outer	(mm)	95
Emission angle	(deg)	45

### Electrical specifications

Illumination extension cable	Extension cable must be ordered separately <a href="#">4</a>	
------------------------------	--	--

#### Continuos mode

Supply voltage	(V)	24
Current	(mA)	600
Power consumption	W	14.4

#### Pulsed mode

Supply voltage <a href="#">1</a>	(V)	36
Max pulse current <a href="#">2</a>	(mA)	1800

### Mechanical specifications

Inner diameter	(mm)	48
Outer diameter	(mm)	100
Height	(mm)	30

### Environment

IP rating	00
-----------	----

## NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

## ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

### COMPATIBLE PRODUCTS



**LTDV1CH-17V**

Strobe controller 1 channel variable current 5 mA - 17A

