

LTZPFL200-00-6-R-24V

LED bar light, 6 LED rows, 200X26.3 illumination area, red, 24V

SPECIFICATIONS

Optical specifications

Light color, peak wavelength	red, 630nm
------------------------------	------------

Lighting area

Length	(mm)	26,3
Width	(mm)	200

Electrical specifications

Illumination extension cable	Extension cable must be ordered separately 4
------------------------------	---

Continuous mode

Supply voltage	(V)	24
Current	(mA)	390
Power consumption	W	9.4

Pulsed mode

Supply voltage 1	(V)	36
Max pulse current 2	(mA)	1170

Mechanical specifications

Length	(mm)	212
Width	(mm)	31,5
Height	(mm)	22

Environment

IP rating	30
-----------	----

NOTES

1. With constant driving voltage (36V recommended, 48V max). Duty cycle = 0-10 %. Max pulse width = 10 ms.
2. With constant driving current. Duty cycle = 0-10 %. Max pulse width = 10 ms.

ORDERING INFORMATION

All accessories including lighting extension cables (CB series) , diffusers (DFLT series) , polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

COMPATIBLE PRODUCTS



TC23130	Bi-telecentric lens for 2/3" detectors, magnification 0.068 x, C-mount
TC13144	Bi-telecentric lens for 1/3" detectors, magnification 0.033 x, C-mount
TC12144	Bi-telecentric lens for 1/2" detectors, magnification 0.044 x, C-mount
TC23144	Bi-telecentric lens for 2/3" detectors, magnification 0.061 x, C-mount



TC2MHR120-C	High resolution telecentric lens for 1" detectors, magnification 0.104x, C-mount
TC2MHR120-F	High resolution telecentric lens for 1" detectors, magnification 0.104x, F-mount
TC2MHR120-E	High resolution telecentric lens for 1" detectors, magnification 0.104x, mount M42X1 FD=16
TC2MHR144-C	High resolution telecentric lens for 1" detectors, magnification 0.089x, C-mount
TC2MHR144-F	High resolution telecentric lens for 1" detectors, magnification 0.089x, F-mount
TC2MHR144-E	High resolution telecentric lens for 1" detectors, magnification 0.089x, mount M42X1 FD=16
TC4MHR120-C	High resolution telecentric lens for 1.2" detectors, magnification 0.143x, C-mount



TC4MHR120-F	High resolution telecentric lens for 1.2" detectors, magnification 0.143x, F-mount
TC4MHR120-E	High resolution telecentric lens for 1.2" detectors, magnification 0.143x, mount M42X1 FD=16
TC4MHR144-C	High resolution telecentric lens for 1.2" detectors, magnification 0.122x, C-mount
TC4MHR144-F	High resolution telecentric lens for 1.2" detectors, magnification 0.122x, F-mount
TC4MHR144-E	High resolution telecentric lens for 1.2" detectors, magnification 0.122x, mount M42X1 FD=16



TC16M144	Telecentric lens for 35 mm detectors, magnification 0.245 x, F-mount
TC16M144-Q	Telecentric lens for 35 mm detectors, magnification 0.245 x, mount M58x0.75 FD = 6.56



TC4K180-F	Telecentric lens for 4k linescan cameras, magnification 0.159x, F-mount
TC4K180-N	Telecentric lens for 4k linescan cameras, magnification 0.159x, mount M42X1 FD=10.56



TC12K192	Telecentric lens for 12k and 16k linescan cameras, magnification 0.320 x, M72 x 0.75 mount
-----------------	--



TCDP2X144	Double magnification bi-telecentric lens, for detectors up to 2/3"
TCDP4X144	Double magnification bi-telecentric lens, for detectors up to 2/3"



MCZR018-004	Macro zoom revolver, C-mount
--------------------	------------------------------



LTDV1CH-17V	Strobe controller 1 channel variable current 5 mA - 17A
--------------------	---



CMLTZPFL	L-bracket, 40x30x12 mm
-----------------	------------------------



DFLTZPFL200-00-6	Diffuser for LED bar light, 6 LED rows, 200X26.3 illumination area
-------------------------	--



PLLTZPFL200-00-6-H	Horizontal polarizer for LED bar light, 6 LED rows, 200X26.3 illumination area
PLLTZPFL200-00-6-V	Vertical polarizer for LED bar light, 6 LED rows, 200X26.3 illumination area