



PT00000400L

Grid pattern

SPECIFICATIONS

Format		Grid
Process		Laser engraving
Substrate		Borofloat glass
Coating	(mm)	Dichroic mirror
Line spacing	(mm)	0.8
Line thickness	(mm)	0.2
Geometrical accuracy	(μ m)	50
Edge sharpness	(μ m)	50

With LTPRHP3W, LTPRXP projectors (circular aperture)

Active area \varnothing	(mm)	11
Number of lines		8 x 8
Max line length	(mm)	7.78

With LTPRSMHP, LTPRSMHP3W projectors (square aperture)

Active area	(mm x mm)	8 x 8
Number of lines		8 x 8
Line length	(mm)	7.78

Mechanical specifications

Diameter	(mm)	21
Thickness	(mm)	1.6 \pm 0.2
Mass	(g)	5

COMPATIBLE PRODUCTS



LTPRHP3W-R	LED pattern projector 3W, HP, red
LTPRHP3W-G	LED pattern projector 3W, HP, green
LTPRHP3W-B	LED pattern projector 3W, HP, blue
LTPRHP3W-W	LED pattern projector 3W, HP, white



LTPRSMHP3W-R	3D LED pattern projector 3W, HP, red
LTPRSMHP3W-G	3D LED pattern projector, 3W, HP, green
LTPRSMHP3W-B	3D LED pattern projector, 3W, HP, blue
LTPRSMHP3W-W	3D LED pattern projector, 3W, HP, white



LTPRXP-R	High Power LED pattern projector, red
LTPRXP-G	High Power LED pattern projector, green
LTPRXP-B	High Power LED pattern projector, blue
LTPRXP-W	High Power LED pattern projector, white

