CBLT021 | DATASHEET

OPTO ENGINEERING

Illumination cable PVC yellow, side 1 M12 male connector straight, side 2 M12 female connector straight, 5 ways, 1m length, high current



Opto Engineering® provides various kinds of cables to match our offer of illuminators, optics, cameras and accessories.
All the cables we offer meet industrial standards of robustness and durability.

RoHS REACH DOSSIER UK CA

SPECIFICATIONS

Electrical specifications

Type		Power and I/O
Number of poles		5
Conductor cross section	(AWG)	18
Cable diameter	(mm)	7
Cable length	(m)	1
Cable insultation material		PVC
Shield		No
Bending cycles	(cycles)	-
Minimum bending radius	(mm)	-
Side 1		M12 5 pins straight plug male connector
Side 2		M12 5 pins straight plug female connector
Other		-
Voltage rating	(VDC)	60
Current rating	(A)	4
IP rating		IP20

Environment

Operating temperature	(°C)	0-40

COMPATIBLE PRODUCTS

Full list of compatible products available *here*.



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.
Data are reported by design, actual lens performance may vary due to manufacturing tolerances.