



# LT3BC250250-W | DATASHEET

## High-power LED backlights with integrated driver



### SPECIFICATIONS

#### Lighting specifications

Illumination area height	(mm)	250
Illumination area width	(mm)	250
Number of LEDs		900
Light color, peak wavelength		white, 5700 K
Spectral FWHM	(nm)	-
Illuminance, continuous <sup>1</sup>	(klux)	109
Irradiance, continuous <sup>1</sup>	(W/m <sup>2</sup> )	314
Illuminance, boosted <sup>1</sup>	(klux)	233
Irradiance, boosted <sup>1</sup>	(W/m <sup>2</sup> )	649
Illuminance, strobe <sup>1</sup>	(klux)	640
Irradiance, strobe <sup>1</sup>	(W/m <sup>2</sup> )	1755
Diffuser		yes
Collimation film		optional

#### Mechanical specifications

Height	(mm)	248.0
Width	(mm)	276.0
Thickness	(mm)	24.0
Mass	(g)	1308
Clamping system		4x M4 threaded holes

#### Environment

Operating temperature	(°C)	0-40
Storage temperature	(°C)	0-50
Operating relative humidity	(%)	20-85, non condensing
Installation		Indoor use only
IP rating		IP54

### KEY ADVANTAGES

#### High-power light output

**Built-in driver** for continuous and strobe operations

#### Industry standard 5 PIN M12 Connector

with PNP/NPN/analog dimming input

#### Optional collimating, polarizing and protective filters

**Compact & robust design** with reduced thickness (24 mm) and thin edges

**Automatic shutdown** in case of overheating

**The LT3BC series** features high-performance LED backlights designed to provide high-power light output, excellent uniformity and contrast thanks to high-efficiency LEDs.

#### Electrical specifications

Operating mode		Continuous and strobe
Supply voltage	(V)	24
Current, continuous	(mA)	2500
Power consumption, continuous	(W)	60
Current, boosted	(mA)	5000
Power consumption, boosted	(W)	120
Peak current, strobe	(mA)	15000
Peak power consumption, strobe	(W)	360
Min pulse duration	(μs)	3
Max pulse duration	(ms)	10
Max duty cycle	(%)	10
Typical pulse delay	(ns)	300
Typical jitter	(ns)	10


I/O interface	PNP logic input, NPN logic input, analog dimming input
Connector	2x M12 straight plug male connector
Included cable	not included

#### Eye safety

Risk group (CEI EN 62471:2010)	Exempt
--------------------------------	--------

<sup>1</sup> At emitting surface.

### CONNECTOR PINOUT



Pin	Function
1	+24Vdc
2	NPN
3	GND
4	PNP
5	Analogue dimming (0-10V)

### COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

### LED color spectrum

