



Pinout :

- +VC: +24 V for continuous illumination. Max current 150 mA
- +VP: +24 V for pulsed illumination. Max current 2800 mA. Max duty cycle 1%. Max Ton 1 ms
- GND: ground

Material		N.A.		Mass		85 g		Scale		2:1			
Surface treatment		N.A.		Part No.		CO29785							
Geometrical tolerance (ISO 2768-2)								Class		K			
Linear tolerance (ISO 2768-2)								Class		m			
0.5	>3±	>6±	>30±	>120	>400±	>1000	>2000	Undimensioned bevels	0.5x45°				
±3	6	30	120	±400	±1000	±2000	±4000	Undimensioned radii	R 0.5				
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2						
				Date		Name		Drawing No.		Sheet			
				Designed		23/01/2020		Rodella		DP 29785-E		1/1	
				Drawn		17/02/2020		Rodella					
Checked		27/02/2020		Bertolucci		<i>Secret and confidential - All rights reserved - No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.r.l. - Any violation shall be legally prosecuted.</i>							
OPTO ENGINEERING S.r.l. - Mantova, Italy - Tel. +39 0376699111 - www.opto-e.com													

all dimensions are in mm